

60,130-1304
OOMRA0192

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

1-19. (Cancelled)

20. (New) A cable arrangement assembly for a vehicle comprising:

a carrier for a cable, said carrier having a first elongate member and a second elongate member, said first elongate member transverse to said second elongate member;

a first cable guide and a second cable guide mounted to said first elongate member;

a third cable guide and a fourth cable guide mounted to said second elongate member;

a first guide rail spaced generally parallel to a second guide rail, said guide rails mountable to said carrier and for guiding a window; and

wherein said carrier has a plate for mounting a drive for a window, said plate having a seal.

21. (New) The cable arrangement assembly of Claim 20 including a drive mounted to said plate, said seal extending around said drive.

60,130-1304
00MRA0192

22. (New) The cable arrangement assembly of Claim 21 wherein said drive comprises a motor.

23. (New) The cable arrangement assembly of Claim 20 wherein said seal is sized larger than an aperture of an inner door panel for receiving said drive.

24. (New) The cable arrangement assembly of Claim 20 including a cable guided by each of said cable guides.

25. (New) The cable arrangement assembly of Claim 24 wherein said cable has a window cursor for attaching a vehicle window to said cable.

26. (New) The cable arrangement assembly of Claim 24 wherein said first elongate member has a first end portion and a second end portion and said second elongate member has a third end portion and a fourth end portion, said first cable guide mounted to said first end portion, said second cable guide mounted to said second end portion, said third cable guide mounted to said third end portion, and said fourth cable guide mounted to said fourth end portion.

27. (New) The cable arrangement of Claim 26 wherein said cable defines a first cable path from said first end portion to said second end portion of said first elongate member and a second cable path from said third end portion to said fourth end portion of said second elongate member.

60,130-1304
OOMRA0192

28. (New) The cable arrangement of Claim 27 wherein said cable defines a third cable path from said first end portion of said first elongate member to said third end portion of said second elongate member and a fourth cable path from said second end portion of said first elongate member to said fourth end portion of said second elongate member.

29. (New) The cable arrangement of Claim 20 including a latch mounting plate for mounting a vehicle door latch on said carrier.

30. (New) The cable arrangement of Claim 20 including a door handle mounting plate for mounting a vehicle door handle on said carrier.

31. (New) The cable arrangement of Claim 20 wherein at least one of said first elongate members and said second elongate members has a u-shaped cross-section.

32. (New) The cable arrangement of Claim 20 including a window supported by said carrier.

33. (New) The cable arrangement of claim 20 wherein said seal is on one face of said carrier and said first guide rail and said second guide rail are on an opposite face of said carrier.

60,130-1304
OOMRA0192

34. (New) A method of assembling a cable arrangement assembly to a vehicle door, comprising the steps of:

A) providing a door inner panel with a window frame, said door inner panel having an interior side and an exterior side, the interior side for facing an interior of a vehicle and the exterior side for facing an exterior of the vehicle;

B) placing a carrier for a cable arrangement for a window on the exterior side of the door inner panel; and

C) mounting the carrier to exterior side of the door inner panel.

69
35. (New) The method of assembly of Claim 34 including the step of:

D) mounting a drive for the window to the carrier.

36. (New) The method of assembly of Claim 35 wherein the door inner panel has an aperture to receive the drive for the window.

37. (New) The method of assembly of Claim 36 including the step of:

F) forming a seal around the aperture of the door inner panel between the door inner panel and the carrier, the seal located on the exterior side of the door inner panel.

60,130-1304
OOMRA0192

38. (New) A vehicle door module comprising:

an inner door panel having a window frame, said inner door panel having an interior side for facing an interior of a vehicle and an exterior side for facing an exterior of the vehicle;

a carrier for a cable for supporting a window of the window frame, said carrier having a first elongate member and a second elongate member, said first elongate member transverse to said second elongate member;

a first cable guide and a second cable guide mounted to said first elongate member;

a third cable guide and a fourth cable guide mounted to said second elongate member;

a first guide rail spaced generally parallel to a second guide rail, said guide rails mountable to said carrier and for guiding the window; and

wherein said carrier has a plate for mounting a drive for the window, said plate having a seal spaced between said carrier and said exterior side of said inner door panel.